

# EVERLUX SUPER BRIGHT LED LIGHT SOURCE MINI



# EVERLUX MINI

**LED 80W 50.000 HOURS LED LIFE**

LED LIGHT SOURCE



**• BRIGHT, WHITE AND POWERFUL**

**• INTERCHANGEABLE FIBER OPTIC CONNECTION COMPATIBLE WITH MAIN BRANDS**



## TECHNICAL SPECIFICATIONS

LED	80 W
LIGHT COLOR TEMPERATURE	5900°K
POWER SUPPLY VOLTAGE	90 - 264 V
N° OF PHASES	1 (SINGLE-PHASE)
FREQUENCY	50 / 60Hz
POWER CONSUMPTION	175 W
CLASS	I
TYPE	B
LED SYSTEM SERVICE LIFE	50.000 HOURS APPROX.
REFRIGERATION	FORCED THROUGH A FAN
OVER TEMP. PROTECTION	AUTOMATIC LED SYSTEM POWER-OFF
DIMMER	ELECTRONIC
FIBER OPTIC CONNECTOR	INTERCHANGEABLE, COMPATIBLE WITH MAIN BRANDS
DIMENSIONS	202 X 290 X 95mm (width x depth x height)
WEIGHT	2.5 Kg.

DISTRIBUTED BY:

COST-EFFECTIVE AS ALL ECLERIS PRODUCTS



ECLERIS  
www.ecleris.com

# EVERLUX SUPER BRIGHT LED LIGHT SOURCE

## PRO

**LED 80 W 50.000 HOURS LED LIFE**



INTEGRATED CONNECTOR FOR OPTIONAL CAMERA

**• BRIGHT, WHITE AND POWERFUL**

**• TURRET FOR FIBER OPTIC CONNECTION COMPATIBLE WITH MAIN BRANDS**



# EVERLUX PRO

## LED LIGHT SOURCE

### TECHNICAL SPECIFICATIONS

LED	80 W
LIGHT COLOR TEMPERATURE	5900°K
POWER SUPPLY VOLTAGE	90 - 264 V
N° OF PHASES	1 (SINGLE-PHASE)
FREQUENCY	50 / 60Hz
POWER CONSUMPTION	175 W
CLASS	I
TYPE	B
LED SYSTEM SERVICE LIFE	50.000 HOURS APPROX.
REFRIGERATION	FORCED THROUGH A FAN
OVER TEMP. PROTECTION	AUTOMATIC LED SYSTEM POWER-OFF
DIMMER	ELECTRONIC
FIBER OPTIC CONNECTOR	BUILT-IN REVOLVING TURRET WITH MULTIPLE ADAPTERS
DIMENSIONS	202 X 290 X 95mm (width x depth x height)
WEIGHT	3.0 Kg.



DISTRIBUTED BY:

## PROCAM VIDEO CAMERA

### TECHNICAL SPECIFICATIONS

RESOLUTION	PAL 625 LINES / NTSC 525 LINES
CCD	1/3"
SHUTTER SPEED	UP TO 1/100.000 SEC.
MAX. ILLUMINATION	2 LUX F1.4
VIDEO OUTPUT	COMPOSITE VIDEO (CVBS) (1 Vpp/75 Ω), BNC S-VIDEO (Y-C), JACK MINI-DIN
ENDODIGI CONNECTOR	MONO JACK 3.5mm
ALL CONTROLS ON HANDPIECE	WHITE BALANCE ANTI-MOIRÉ (FOR FLEXIBLE SCOPES) WINDOW PHOTO

COST-EFFECTIVE AS ALL ECLERIS PRODUCTS